

## Vierkantstahl, gewalzt

DIN EN 10059 bzw. DIN 7527/BI. 6  
in Herstellungslängen von 4 bis 6m

	kg/m	W.-Nr.	W.-Nr.	W.-Nr.	W.-Nr.	W.-Nr.	W.-Nr.	W.-Nr.
mm		1.4301	1.4305	1.4435	1.4539	1.4541	1.4571	1.4841
6x6	0,28							x
8x8	0,5	x		x		x	x	x
10x10	0,79	x		x	x	x	x	x
12x12	1,13	x		x	x	x	x	x
14x14	1,54	x				x	x	
15x15	1,77	x		x	x	x	x	x
16x16	2,01	x		x		x	x	
18x18	2,54	x		x		x	x	
20x20	3,14	x		x	x	x	x	x
22x22	3,80	x		x		x	x	
25x25	4,91	x		x	x	x	x	x
28x28	6,15			x				
30x30	7,07	x		x	x	x	x	x
32x32	8,04	x				x	x	
35x35	9,62	x		x	x	x	x	x
40x40	12,56	x	x	x	x	x	x	x
45x45	15,90	x		x		x	x	
50x50	19,63	x	x	x	x	x	x	x
55x55	23,75	x				x	x	
60x60	28,28	x	x	x	x	x	x	x
65x65	33,17	x		x		x	x	
70x70	38,46	x		x		x	x	
75x75	44,20	x		x		x	x	
80x80	50,24	x	x	x	x	x	x	x
85x85	56,72	x		x		x	x	
90x90	63,58	x	x	x	x	x	x	
100x100	78,50	x	x	x	x	x	x	
110x110	94,99		x					
120x120	113,00	x	x			x	x	
135x135	143,10	x				x	x	
140x140	153,90							
150x150	176,60	x	x			x	x	
160x160	201,00						x	
180x180	254,30						x	
200x200	271,90						x	